Simulation of Magnetic Flux Distribution of Stator and Rotor Coil of Superconducting Air Cored Wind Turbine Generator Using COMSOL Multiphysics

COMSOL CONFERENCE INDIA 2012

Presented By Abhik Hazra Power Engg. Dept. Jadavpur University. Kolkata, Eest Bengal

Energy & Civilization

Energy is the ability to do work


Obligatory part of mankind on the Earth

Moves a nation, invites its prosperity

Forms of Energy


Heat Energy





Chemical Energy





Nuclear Energy





Energy Conversion

Energy can be changed from one form to another

 Energy can be neither created nor destroyed by ordinary means

The Sun: a giant energy factory

 Almost all of the energy we use comes from the sun

Primary & Secondary source of energy

Renewable & Nonrenewable source of energy

Electricity: The green st form of energy

Compact & clean form of energy

Efficient transmission

Efficiently usable

Different Electricity generation Methodologies

- From Fossil Fuel: Coal, Mineral oil, Natural Gas
 - Harmful To nature
 - Reduced reserves : Only for some years
- From Nuclear Energy: Environmental hazards, radiation

 From Renewable Energy recourses: Solar, Wind, Geo Thermal, Tidal, Bio-Gas, etc.

Wind Energy

A Renewable Primary Source of energy

Cause of wind flow

Energy contained in wind

Wind energy converter: converts wind power into electricity

Electricity Generation from Wind

- Pollution free Green Methodology
- Continuously increasing popularity
- More effectiveness in large size wind turbine generator (> 5 MW WTG will produce more than 5 GW world wide by the year 2020)
- Offshore installation for better wind profile


Direct Drive High Temperature Superconducting Wind Turbine Generator

- No Gear Box : Light weight
- Low Speed Generator needed
- HTS Generator : High magnetic Flux
 - High Power density
 - Power Generation in low RPM
 - Reduced Weight
- Recent trend of designing WTG

Selected HTS WTG Model

- Circular Superconducting Field Coil: Uniform
 Stress
- Air Core: Reduced weight
- Both Radial and Axial Field coil
- Conventional copper Stator Coil
- 10 pole, 5 m diameter machine to achieve a class of 10 MW

Generator Model



Use of Comsol Multiphysics


- Model Geometry Was created by inbuilt 3D cad tool
- Material properties were assigned
- AC/DC module was selected as physics setting
 - Magnetic and Electric field
 - AV Formulation
- Study portal : Stationary Study
- Animation

Meshing of the Model


Tetrahedral Mesh: 3D mesh element

- Different size of mesh element
 - Finer mesh for superconducting coil surface
 - Fine mesh for stator coil
 - Coarser mesh for surrounding air


Meshing of the Model



Simulation of Magnetic Flux Distribution



Comparative Study



Animation

